



CONTRACTOR SERIES

2-WAY IN-WALL FRAMELESS LOUDSPEAKERS

LDCFL52 / LDCFL52100V

LDCFL62 / LDCFL62100V

SPECIFICATIONS / TECHNISCHE DATEN / CARACTÉRISTIQUES TECHNIQUES / CARACTERÍSTICAS TÉCNICAS / PRZYŁĄCZA, WYMIARY I MONTAŻ / DATI TECNICI

EN

Model Name:	LDCFL52	LDCFL52100V	LDCFL62	LDCFL62100V
Product Type:	in-wall speaker	in-wall speaker	in-wall speaker	in-wall speaker
Type:	passive	passive	passive	passive
Version:	wall installation speaker	wall installation speaker	wall installation speaker	wall installation speaker
Speaker Type:	2-way speaker	2-way speaker	2-way speaker	2-way speaker
Colour:	white	white	white	white
Woofer Size:	5.25"	5.25"	6.5"	6.5"
Woofer Size:	133 mm	133 mm	165 mm	165 mm
Tweeter Size:	1.2"	1.2"	1.2"	1.2"
Tweeter Size:	30 mm	30 mm	30 mm	30 mm
Opening Size:	Ø 178 mm	Ø 178 mm	Ø 210 mm	Ø 210 mm
Mounting Depth:	77 mm	77 mm	81 mm	81 mm
Min. Material Thickness:	3 mm	3 mm	3 mm	3 mm
Max. Material Thickness:	15 mm	15 mm	15 mm	15 mm
Impedance (low-impedance):	8 ohms	n/a	8 ohms	n/a
100 V Connection Values:	n/a	1.5 W / 3 W / 6 W	n/a	6 W / 12 W / 24 W
Low-impedance Rated Load (RMS):	40 W	40 W	60 W	60 W
Sensitivity (1 W / 1 m):	88 dBspl	88 dBspl	88 dBspl	88 dBspl
Frequency Response:	80 Hz - 20 kHz	80 Hz - 20 kHz	70 Hz - 20 kHz	70 Hz - 20 kHz
Controls:	Switch for tweeter level (-, neutral position, +)	Switch for tweeter level (-, neutral position, +)	Switch for tweeter level (-, neutral position, +)	Switch for tweeter level (-, neutral position, +)
Depth:	81 mm	81 mm	86 mm	86 mm
Diameter:	204 mm	204 mm	234 mm	234 mm
Weight:	1.09 kg	1.23 kg	1.56 kg	1.87 kg
Other Features:	frameless design	frameless design	frameless design	frameless design