




PC-1868W-EB

Ceiling mount speaker



**Easy installation.
Versatile use.**

sound without compromise

www.toa.eu

PC-1868W-EB

Ceiling mount speaker

Designed for simple installation, the TOA PC-1868W-EB ceiling mount speaker is equipped with a metal grille an ABS resin Baffle. The finely crafted design with thin panel does not detract from venue architecture or interior decor.

The speaker can be easily installed thanks to its spring catch method — this saves time and money. It is ideal for use in any kind of public building where pagings and BGM are broadcasted.

- Flat front panel
- Quick and easy installation
- 12 cm speaker


Specifications

| | PC-1868W-EB |
|---------------------------|---|
| Rated Input | 6W (for 100V line), 3W (for 70V Line) |
| Rated Impedance | 100V line: 1.7kΩ (6W), 3.3kΩ (3W), 10kΩ (1W) (Internal wiring must be changed) 70V line: 1.7kΩ (3W), 3.3kΩ (1.5W), 10kΩ (0.5W) (Internal wiring must be changed) |
| Sound Pressure Level | 90 dB (1W, 1 m, 330 – 3,300Hz Pink noise) |
| Frequency Response | 100Hz – 16kHz |
| Speaker Component | 12 cm cone-type |
| Mounting Method | Spring catch |
| Applicable Cable | Solid copper wire or 7-core twisted copper wire, More than $\varnothing 0.8$ mm or 0.5 mm ² or more |
| Finish | Baffle: ABS resin, pure white (RAL 9016 or its equivalent) Grille: Net, pure white, paint (RAL 9016 or its equivalent) |
| Dimensions | 180 x 11 (exposed section) + 110 (D)mm |
| Dimension for Fixing Hole | $\varnothing 150$ (mounting hole) x 50 (maximum ceiling thickness)mm |
| Weight | 675g (bracket included) |

Application examples



Shopping center



Hotels



Schools



Retail stores



Hospitals



Exhibition halls



Mounting diagram

