

CCS 1000 D Discussion Devices

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Unique patent pending possible-to-speak indicator
- ▶ Plug and play functionality for ensuring fast installation and reconfiguration times
- ▶ Compact, attractive ergonomic design
- ▶ Easily configured as a participant device or chairperson's device
- ▶ Immunity to mobile phone interference

Discussion Devices are connected in a daisy-chain configuration to the Control Unit of a CCS 1000 Digital Discussion System. Their plug-and-play functionality allows them to be conveniently connected to and removed from the system as required. A power down or restart of the system is not necessary, which ensures for fast installation and reconfiguration times. Participants can take part in a discussion by speaking into the microphone and listening to proceedings through the built-in loudspeaker or (optional) headphones.

Functions

Possible-to-speak indication

A white possible-to-speak indicator above the microphone button indicates when the microphone can be activated.

Request-to-speak indication

A green request-to-speak indicator above the microphone button and in the head of the microphone indicate when a request-to-speak has been added to the waiting list. The indicators flash green when the request-to-speak is first in the waiting list.

Short or long microphone with flexible stem

The fixed microphone with flexible stem can be easily adjusted to suit the user. For maximum comfort, a short 310 mm (12.2 in) or long 480 mm (18.9 in) microphone stem is available.

Built-in loudspeaker with volume control

To ensure for optimum intelligibility, the loudspeaker volume of all Discussion Devices is centrally controlled from the Control Unit.

Face-to-face meeting feeling

An authentic face-to-face meeting feeling is achieved by allowing the loudspeaker and microphone to be on at the same time.

Headphones socket

The built-in 3.5 mm (0.14 in) stereo headphones socket enables the speaker to be clearly heard, even when there is excessive background noise.

Built-in volume control for headphones

For maximum comfort, the headphones volume can be adjusted by means of a rotary thumbwheel on the side of the Discussion Device. To prevent acoustic feedback from headphones to microphone, an option in the web browser application can be set to automatically reduce the headphones volume when the microphone is activated.

GSM immunity

Immunity to mobile phone interference ensures for clear, uninterrupted discussion.

Configurable as a participant or chairperson's device

The Discussion Device can be quickly configured as a 'chairperson's device', which enables a user to function as the chairperson at a meeting. No restart of the system is required. During a discussion, the chairperson can press and hold in the priority button to overrule all participant microphones. A chime is also sounded to announce that the chairperson is about to speak.

Controls and Indicators

- Microphone button
- Color-coded LED indicator above microphone button for showing the following states: microphone on, request-to-speak, and possible-to-speak
- Light-ring indicator in head of microphone
- Rotary thumbwheel on side of device for adjusting the headphones volume
- Concealed initialization button at base of device for reassigning the network address
- Concealed slide-switch at base of Discussion Device for configuring the Discussion Device as a 'participant Discussion Device' or 'chairperson's Discussion Device'
- Chairperson's configuration only – separate microphone button and 'priority button'

Connections

- 1 x 6-pole circular female connector with cable locking recess – for loop-through connection of Discussion Devices
- 1 x 3.5 mm (0.14 in) stereo headphones socket on side of device
- 1 x 2 m (78.7 in) cable with a 6-pole circular male connector with cable lock

Certifications and approvals

EU	CE, WEEE
US	FCC
CA	ICES-003
KR	KCC
AU/NZ	RCM
RU/KZ/BY	EAC
CN	China RoHS
SA	SASO

Installation/configuration notes

All Discussion Devices are delivered with a participant's microphone button, which can be easily exchanged for a set of chairperson's buttons. Two sets of chairperson's buttons and a special tool for removing the buttons are supplied with each Control Unit of a CCS 1000 Digital Discussion System. To

complete the configuration of the Discussion Device the concealed slide switch at the base of the Discussion Device has to be set from 'participant' to 'chairperson'.

Technical specifications**Electrical**

Frequency response	200 Hz to 12.5 kHz
Headphones load impedance	> 32 ohms < 1k ohm
Loudspeaker nominal output	72 dB SPL

Mechanical

Dimensions device without microphone (H x W x D)	64 x 203 x 146 mm (2.5 x 8.0 x 5.7 in)
Height with microphone in horizontal position	130 mm (5.1 in)
Length of microphone from mounting surface	CCSD-DS: 310 mm (12.2 in) CCSD-DL: 480 mm (18.9 in)
Weight	Approx. 1 kg (2.2 lb)
Mounting	Tabletop (portable or fixed)
Material (top)	Plastic ABS+PC
Material (base)	Metal ZnAl4
Color (top)	Traffic black (RAL 9017) matt-gloss
Color (base)	Pearl light grey (RAL 9022) matt-gloss

Environmental

Operating temperature	0 °C to +35 °C (+32 °F to +95 °F)
Storage temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative humidity	15% to 90%
Air pressure	600 to 1100 hPa

Ordering information**CCS 1000 D Discussion Device Short**

Discussion Device for the CCS 1000 Digital Discussion System, supplied with short-stem fixed microphone, configurable as a delegate device or chairperson's device.

Order number **CCSD-DS**

CCS 1000 D Discussion Device Long

Discussion Device for the CCS 1000 Digital Discussion System, supplied with long-stem fixed microphone, configurable as a delegate device or chairperson's device.

Order number **CCSD-DL**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com