

## eGPA4-150

LOW IMPEDANCE

*Multichannel Amplifier*



### PRODUCT OVERVIEW

ECLER ESSENTIALS eGPA4-150 is a 4x150 W RMS @ 4 Ω, high efficiency multichannel amplifier (class D). Auto stand-by function and fanless design, 100% silent. Thermal and overload protections. Anti-clip system.

### KEY FEATURES

- 4 analogue audio inputs x 4 powered audio outputs
- Euroblock input and output connectors
- High efficiency, auto standby function and convection cooling (fanless, 100% silent)
- BRIDGE mode ready
- Thermal protection
- Overload protection
- Anti-clip system

### APPLICATIONS

- Clubs
- Theme restaurants
- Discos
- Leisure centres
- Cinemas and theatre
- Educational centres
- Boardrooms and conference halls
- Sports centres
- Mobile outdoor applications

### CERTIFICATIONS

- EN60065:2014
- EN55103-1:2009
- EN55103-2:2009
- 2006/95/EC
- 2004/108/CE

TECHNICAL SPECIFICATIONS

eGPA4-150

POWER 20-20kHz 1% THD

1 Channel @ 4Ω	148 WRMS
1 Channel @ 8Ω	74 WRMS
All Channels @ 4Ω	145 WRMS
2 Bridged Channels @ 8Ω	290 WRMS
Frequency response (-1 dB, -3dB)	20Hz - 25kHz
Filter (High-Pass) 3rd order Butterworth	15Hz
THD+Noise @ 1kHz Full Power	<0.05%
S+N/N 20Hz - 20kHz @ 1W/4Ω	>85dB
CMRR	>55dB
Damping factor 1kHz @ 8Ω	>150
Channel crosstalk @ 1kHz	>55dB
Input Sensitivity / Impedance	0dB/>20kΩ
Anticlip @ 2dBV input	<1% THD
Mains voltage	100-240VAC



Power consumption

pink noise, 1/8 power @ 4Ω	113W / 130VA
pink noise, 1/3 power @ 4Ω	268W
Idle	29W
STBY	18W
Efficiency @ Pmax	80%

General

Dimensions (Handle excluded)	440x44x221mm
Weight	3.70kg

MECHANICAL DIAGRAM





All product characteristics are subject to variation due to production tolerances. **NEEC AUDIO BARCELONA S.L.** reserves the right to make changes or improvements in the design or manufacturing that may affect these product specifications.

For technical requests address to your supplier, distributor or fill the contact form in our website, at Support / Technical Request.

Motors, 166-168 08038 Barcelona - Spain - (+34) 932238403 | [information@ecler.com](mailto:information@ecler.com) | [www.ecler.com](http://www.ecler.com)