

# ZX1



**ZX1-90**

PASSIVE / FULL RANGE CABINET  
90° x 50° COVERAGE PATTERN  
IMPEDANCE: 8 OHMS  
POWER: 300 WATTS



**Incredible**Sound

# It's your music, your voice, your message.

**You need a speaker that can reproduce every note, every inspirational word and every nuance of your style. Introducing ZX1. Compact, lightweight, yet high performance, ZX1 is a reflection of the needs of the high-speed,**

**time-crunched, high-tech lifestyle you lead. Its versatility is matched only by your imagination, and its look is pure beauty. So while your audience may not be fully aware**

**of why you sound incredible, you'll know it's because you chose the very best...**

# ZX1



**ZX1** offers a wide array of mounting options including an integrated pole mount and removable rubber feet that hide M8 mounting studs. Dual NL4 connectors and an ergonomic molded carrying slot make **ZX1** perfect for portable music, AV rental and mobile audio applications.

**ZX1** shines in monitor wedge applications, especially where the reproduction of vocal frequencies is crucial. Its asymmetrical cabinet design means you simply have to put **ZX1** on its side to achieve a 45° monitor angle. And with the ability to rotate its 90° x 50° horn, you can adjust the dispersion pattern to suit your unique application.

	<b>ZX1-90</b> <b>Portable Version</b>	<b>ZX1i-90</b> <b>Fixed Install Version</b>	<b>ZX1i-100</b> <b>Fixed Install Version</b>	<b>ZX1i-100t</b> <b>70v/100v Version</b>
<b>Frequency Response<sup>(1)</sup></b> <b>(-3 dB)</b>	60 Hz - 20 kHz	60 Hz - 20 kHz	60 Hz - 20 kHz	60 Hz - 20 kHz
<b>Frequency Range<sup>(1)</sup></b> <b>(-10 dB)</b>	48 Hz - 20 kHz	48 Hz - 20 kHz	48 Hz - 20 kHz	48 Hz - 20 kHz
<b>Axial Sensitivity<sup>(1)</sup></b>	94 dB (1W/1m)	94 dB (1W/1m)	92 dB (1W/1m)	92 dB (1W/1m)
<b>Maximum Calculated SPL</b>	123 dB	123 dB	121 dB	121 dB
<b>Horizontal Coverage</b>	90° or 50°	90° or 50°	100°	100°
<b>Vertical Coverage</b>	50° or 90°	50° or 90°	100°	100°
<b>System Power Handling</b>	200W Continuous, 400W Program	200W Continuous, 400W Program	200W Continuous, 400W Program	200W Continuous, 400W Program
<b>LF Transducer</b>	EV8L, 8 in (203mm) Driver	EV8L, 8 in (203mm) Driver	EV8L, 8 in (203mm) Driver	EV8L, 8 in (203mm) Driver
<b>HF Transducer</b>	DH2005, 1 in. (25.4mm) Exit Compression Driver	DH2005, 1 in. (25.4mm) Exit Compression Driver	DH2005, 1 in. (25.4mm) Exit Compression Driver	DH2005, 1 in. (25.4mm) Exit Compression Driver
<b>Nominal Impedance</b>	8 Ohms	8 Ohms	8 Ohms	8 Ohms
<b>Pole Mount</b>	Included	N/A	N/A	N/A
<b>Transformer Taps</b>	N/A	N/A	N/A	6.5, 12.5, 25, 50, 100 watts 70/100v
<b>Connectors</b>	Two NL4 Connectors	4-Pin detachable Phoenix style	4-Pin detachable Phoenix style	4-Pin detachable Phoenix style
<b>Overload Protection</b>	Full protection - all modes	Full protection - all modes	Full protection - all modes	Full protection - all modes
<b>Mounting System</b>	Four M8 studs on bottom of speaker	QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket	QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket	QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket
<b>Built-In Monitor Angle</b>	Yes	No	No	No
<b>Available Colors</b>	Black	Black/White	Black/White	Black/White
<b>Included Accessories</b>	None	QuickSAM™ Mount	QuickSAM™ Mount	QuickSAM™ Mount
<b>Dimensions (H x W x D)</b>	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm
<b>Net Weight</b>	8.4 kg (18.5 lbs)	8.4 kg (18.5 lbs)	8.4 kg (18.5 lbs)	10.4 kg (23.0 lbs)
<b>Shipping Weight</b>	10.2 kg (22.5 lbs)	10.2 kg (22.5 lbs)	10.2 kg (22.5 lbs)	12.3 kg (27.0 lbs)

(1) Half-space measurements

## The Complete ZXI Family

The ZXI is part of a complete compact speaker system product line with models for fixed installation distributed systems.



### Americas

Telex Communications Inc.  
12000 Portland Ave South,  
Burnsville, MN 55337, USA  
USA — Phone: 1-800-392-3497, Fax: 1-800-955-6831  
Canada — Phone: 1-866-505-5551, Fax: 1-866-336-8467  
Latin America — Phone: 1-952-887-5532, Fax: 1-952-736-4212

### Europe, Africa & Middle-East

Germany: EVI Audio GmbH.  
Hirschberger Ring 45, D 94315,  
Straubing, Germany  
Phone: +49 9421 706-0, Fax: +49 9421 706-265

France: EVI Audio France S.A.,  
Parc de Courcerin,  
Allée Lech Walesa,  
F 77185 Lognes, France  
Phone: +33 1-6480-0090  
Fax: +33 1-6006-51-3

UK: Shuttlesound,  
4 The Willows Centre,  
Willow Lane, Mitcham,  
Surrey CR4 4NX, UK  
Phone: +44 208 646 7114  
Fax: +44 208 245 5666

### Asia & Pacific Rim

Japan: EVI Audio Japan Ltd.  
5-3-8 Funabashi, Setagaya-Ku,  
Tokyo, Japan 156-0055  
Phone: +81 3-5316-5020,  
Fax: +81 3-5316-5031

China: Telex EVI Audio (Shanghai) Ltd.  
Room 2210-2215,  
Tower B, Far East International Plaza  
No. 317, Xianxia Road,  
Shanghai, China, PC: 200051  
Phone: +86 (21) 6235-1677  
Fax: +86 (21) 6235-1676

Hong Kong: Telex EVI Audio (HK) Ltd.  
Unit 5,1/F, Topsail Plaza  
11 On Shum Street  
Shek Mun, Shatin HK  
Phone: +852 2351-3628, Fax: +852 2351-3329

Singapore: Telex Pte. Ltd.  
3015A Ubi Road 1, 05-10  
Kompong Ubi Industrial Estate, Singapore 408705  
Phone: +65 6746-8760, Fax: +65 6746-1206

Live For Sound™  
www.electrovoice.com

